

Defender Automatic Rising Kerb

SPECIFICATION

Widths Available
2.0M to 5m in 0.5M increments

Rising Element Height
340mm, 500mm and 800mm

Maximum Axle Weight
12 tonnes

Operating Time
1.5 - 8 seconds

DRIVE UNIT
Remote hydraulic pack with 3 phase motor (inverter driven)

Control System
Schneider PLC

Cycles
100% Duty Rating

POWER SUPPLY
230VAC 50Hz 10 Amp

Construction
All welded steel RHS

Cover Plates
8mm Durbar (mechanically fixed)

Finish
Rising Element: Epoxy primed and polyester powder coated,
Lower Frame: Galvanised



PLC

Controlled by a Schneider PLC system with inverter, all pre wired and factory tested ready for connection to your mains power supply.



BLOCKER DRIVE

Hydraulic system with inverter driven three phase pump.



VISUAL DETERRENT

A road blocker is the ultimate barrier to unwanted or unauthorised vehicle entry. It's forbidding looks provide a visual deterrent and the inherent strength will prevent any vehicle borne attack. Blockers are commonly placed behind swing or sliding gates for the ultimate in protection.



FINISH

The rising element is powder coated in high visibility yellow with black chevrons to the attack face. The lower framework is fully hot dip galvanised after fabrication.

